

Static Pressure Kit



RoHS
Compliant

Pressure Conversions

| Multiply | By | Equals |
|------------|-------|---------|
| In. of H2O | 1.868 | mmHG |
| In. of H2O | 0.074 | In HG |
| In. of H2O | 0.249 | kPa |
| In. of H2O | 249.1 | Pascals |
| In. of H2O | 2.491 | mBar |
| In. of H2O | 0.036 | Psi |
| In. of H2O | 25.40 | mmH2O |

Features

- Dual input differential measurement to ± 60 inches water column
- Triple Scale: inches water column (In-WC), mBar, and PSI
- MIN/MAX value capture
- Data hold
- Backlit display
- Ruggedized, including rubber boot with integral magnet
- Auto power-off
- 3 Year limited warranty

Includes

- Dual Input Electronic Manometer (EM201E)
- 2 Magnetic static pressure tips (ASP1)
- 2 Brass valve fitting connector (BF100)
- Soft carrying case (AC319)
- Pressure tubing
- 9V Battery

Specifications

- Measurement range: $-60'' \sim +60''$ WC
 $-100 \sim +100$ mBar
- Accuracy: $\pm 0.03''$ WG < $3''$ WC
 $\pm 1\%$ RDG > $3''$ WC
- Resolution: $0.001'' - 9.999'' \sim +9.999''$ WC
 $0.01''$ for < $-10''$ or > $+10''$ WC
- Operating range: $32^\circ \sim 104^\circ$ F ($0^\circ - 40^\circ$ C),
10 ~ 90% RH
non condensing
- Battery Life: 40 hours min with
alkaline battery

Distributed by:
Valuetesters.com
sales@valuetesters.com
Tel: 602-795-8292, Fax: 602-795-4624