



Distributed by:
Valuetesters.com
sales@valuetesters.com
Tel: 602-795-8292, Fax: 602-795-4624

AM-140-A Precision TRMS Digital Multimeters with PC Connection

These TRMS Commercial grade digital multimeters offer more features, better accuracy at a great price. TRMS, accuracy to 0.02%, frequency, capacitance, duty cycle, analog bar graph, PC interface and large backlit displays are just a handful of features that are available on these meters.

- True RMS (TRMS)
- Measurements: Voltage up to 1000V AC/DC, Resistance, AC/DC Current, Frequency, Capacitance, Duty Cycle
- Optical isolated PC interface capability
- Crest (Peak hold), MAX, MIN MAX-MIN recording
- Auto and manual ranging
- Intelligent auto power off
- Data hold
- Relative zero mode
- Audible and visual warning against improper plug-in
- DC Loop Current 4-20mA
- dBm reading with 20 selectable impedance values
- Backlight display
- Large, easy to read large LCD display
- High speed analog bar graph
- Diode Test
- 4-20mA DC loop current
- Audible continuity
- Safety CAT IV 600V, CAT III 1000V

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)



General Specifications

Display	4-4/5 digits 50,000 counts. Selectable stable mode 5-4/5 digits 500,000 counts for DC voltage, & 6 digits 999,999 counts for HZ
Polarity	Automatic
Update Rate	4-4/5 digits fast mode: 5 per second nominal; 5-4/5 digits stable mode: 1.25 Per second nominal;
42 Segments Bar Graph	60 per second max
Operating Temperature	0°C to 45°C (32°F to 113°F)
Relative Humidity	Maximum relative humidity 80% for temperature up to 31°C decreasing linearly to 50% relative humidity at 45°C
Pollution Degree	2
Storage Temperature	-20°C to 60°C (-4°F to 140°F), < 80% R.H.(With battery removed)
Altitude	Operating below 2000m
Temperature Coefficient	Nominal 0.1 X (specified accuracy)/ °C @ (0°C -18°C or 28°C -- 40°C/32°F - 104°F), or otherwise specified
Sensing	AC, AC+DC true RMS
Safety	Double insulation per IEC61010-1 2nd ed., EN61010-1 2nd ed., UI61010-1 2nd ed. & Can/csa c22.2 No. 61010.1-0.92 To category III 1000v AC & DC and category IV 600V AC & DC
Terminals (To Com)	V : Category III 1000 VAC & VDC and category IV 600 VAC & VDC.
Measurement Category	A / mA: Category III and category IV 600 VAC and 300 VDC.
Overload Protections	µA & mA: 1A/600V, IR 10kA or better, F fuse A: 10A/600V, IR 100kA or better, F fuse V: 1050VRMS, 1450VPEAK mV, e, & others: 600 VDC & VAC RMS
Transient Protection	8kV (1.2/50µS SURGE)
E.M.C.	Meets EN61326-1:2006 (EN55022, EN61000-3-2, EN61000-3-3, EN61000-4-2, EN61000-4-3, EN61000-4-4, EN61000-4-5, EN61000-4-6, EN61000-4-8, EN61000-4-11)
In an RF field of 3V/m:	Capacitance function is not specified
Other Function Ranges	Total accuracy = specified accuracy + 100 digits. Performance above 3V/m is not specified
Power Supply	Single alkaline 9V battery; nEDA1604a, JIS6AM6 or IEC6LF22
Power Consumption	6mA typical
Low Battery	Below approx. 7V
Apo Timing	Idle for 17 minutes
Apo Consumption	55µA typical
Dimension	L317.6 x W177.8 x H76.2mm (12.5 x 7 x 3in) with clamshell
Weight	635g (1.4lb) with clamshell

Distributed by:


sales@valuetesters.com
 Tel: 602-795-8292, Fax: 602-795-4624



AM-140-A Precision TRMS Digital Multimeters with PC Connection

Data Sheet

Electrical Specification

	Range	Accuracy
AC Voltage	500.00 mV 5.0000 / 50.000 / 500.00 / 1000.0 V	+/- (0.08% Rdg + 60 LSD) @ 45 to 300 Hz**
DC Voltage	500.00 mV 5.0000 / 50.000 / 500.00 / 1000.0 V	+/- (0.03% Rdg + 2 LSD) @ 0 to 50V**
Resistance	500.00 Ohms 5.0000 / 50.000 / 500.00 kOhms 5.0000 / 50.00 0MOhms	+/- (0.10% Rdg + 6 LSD) @ 500 Ohms to 500 kOhms ranges **
AC Current	500.00 / 5000.0 uA 50.000 / 500.00 mA 5.0000 / 10.000 A	+/- (1.0% Rdg + 40 LSD) @ 50 and 60 Hz**
DC Current	500.00 / 5000.0 uA 50.000 / 500.00 mA 5.0000 / 10.000 A	+/- (0.5% Rdg + 20 LSD)
Frequency	5.0000 Hz to 200.000kHz	+/- (0.002% Rdg + 4 LSD)
Capacitance	50.00 / 500.0 nF 5.000 / 50.00 / 500.0 / 9999uF	+/- (2.0% Rdg + 3 LSD) @ 50 nF to 50uF ranges**
Duty Cycle	0.1% to 99.99%	+/- (3 LSD / kHz + 3 LSD)

Diode Tester

Range	5.0000V
Accuracy	1%+1D
Test Current (Typical)	0.4mA
Open Circuit Voltage	<3.5VDC

Optional Accessories	Part Number
PC Interface Kit (PC connection cable with software)	USB-KIT3
Software	www.amprobe.com
Carrying Case	CC-ACDC

Replacement Parts (supplied with product)	Part Number
Test Leads With Set Of Alligator Clips (alligator clips are not supplied with product)	MTL-90B
Instruction Manual	www.amprobe.com

Distributed by:
 **Valuetesters.com**
sales@valuetesters.com
Tel: 602-795-8292, Fax: 602-795-4624

AM-140-A Precision TRMS Digital Multimeters with PC Connection

Data Sheet



Distributed by:
Valuetesters.com
sales@valuetesters.com
Tel: 602-795-8292, Fax: 602-795-4624

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0