

## EX205T & EX210T True RMS MultiMeters



Both models are autoranging True RMS meters providing a more accurate reading when measuring distorted waveforms. EX210T with built-in IR Thermometer allows for quick non-contact Temperature measurements.



### Features

- True RMS for better accuracy when measuring distorted waveforms
- Patented built-in IR Thermometer with laser pointer for locating hot spots with 4:1 Distance to Target Ratio (EX210T model only)
- 2000 count large backlit dual LCD with easy-to read digits
- Low current capability with resolution to 0.1μA
- Max Hold
- Input fuse protection
- Auto power off and Data Hold
- Complete with test leads and 9V battery

| Specifications               | Range                      | Max Resolution |
|------------------------------|----------------------------|----------------|
| AC Voltage                   | 600V                       | 0.1mV          |
| DC Voltage                   | 600V                       | 0.1mV          |
| Basic Accuracy (VDC)         | ±0.5%                      |                |
| AC Current                   | 10A                        | 0.1μA          |
| DC Current                   | 10A                        | 0.1μA          |
| Resistance                   | 20MΩ                       | 0.1Ω           |
| IR Temperature (EX210T only) | -5 to 446°F / -20 to 230°C | 0.1°           |
| Continuity / Diode           | Yes                        |                |
| Dimensions                   | 5.8x2.9x1.6" (147x76x42mm) |                |
| Weight                       | 9.17oz (260g)              |                |

### Ordering

EX205T ..... True RMS Autoranging MultiMeter  
 EX205T-NIST ..... EX205T with Certificate of Calibration Traceable to NIST  
 EX210T ..... True RMS Autoranging MultiMeter + IR Thermometer  
 EX210T-NIST ..... EX210T with Certificate of Calibration Traceable to NIST

Distributed by:  
**Valuetesters.com**  
 sales@valuetesters.com  
 Tel: 602-795-8292, Fax: 602-795-4624

