

# Competitive Features

## REFRIGERANT RECOVERY MACHINES



	<b>Fieldpiece MR45</b>	<b>Appion G5</b>	<b>Robinair Promax RG6</b>	<b>Inficon Vortex Dual</b>	<b>CPS TR600</b>	<b>JB F6</b>	<b>Ritchie YJ-LTE/95730</b>	<b>Bacharach Eco 2020</b>
Variable speed Motor	●							
DC Motor	●							
Low Voltage Operation	●							
Digital Display	●							
Onboard Diagnostics	●							
Self Purge	●		●	●		●	●	●
Water Resistant*	●							
Cord Storage	●							
Auto Shut Off at Completed Recovery (Low pressure shut off)	●				●			
Motor Horsepower	1 HP	1/2 HP	3/4HP	1 HP	2/3 HP	1 HP	1/2 H	1 HP
Motor RPMs	3000	1710	N/A	N/A	N/A	1425	1725	1750
Weight	22lbs	24lbs	27lbs	30lbs	28lbs	30lbs	24lbs	28.5lbs
Warranty	1-year	1-year	1-year	3-year	1-year	3-years	1-year	1-year

Disclaimer: The information found within this chart is not reflective of all competitors. All trademarks and copyrights on this page are owned by their respective owners. Data collected from technical specification literature available through the worldwide web and other publicly available marketing literature. © 2017 Fieldpiece Instruments. All Rights Reserved.

\*IP24



Distributed by:  
**Valuetesters.com**  
 sales@valuetesters.com  
 Tel: 602-795-8292, Fax: 602-795-4624

[www.fieldpiece.com](http://www.fieldpiece.com)



# Competitive Flow Rates REFRIGERANT RECOVERY MACHINES

**90% VAPOR**  
**10% LIQUID**  
Typical % of time spent during recovery



		<b>Fieldpiece MR45</b>	<b>Appion G5</b>	<b>Robinair Promax RG6</b>	<b>Inficon Vortex Dual</b>	<b>CPS TR600</b>	<b>JB F6</b>	<b>Ritchie YJ-LTE/95730</b>	<b>Bacharach Eco 2020</b>
<b>R22</b>	<b>High Temp Vapor Rate</b>	<b>0.88 / (0.40) Fastest</b>	0.59 / (0.28*)	0.46 / (0.21)	0.62 / (0.28)	0.86 / (0.390*)	0.57 / (0.26)	0.29 / (0.13)	0.60 / (0.27)
	<b>Direct Vapor</b>	0.62 / (0.28)	0.62 / (0.28)	0.53 / (0.24)	0.53 / (0.24)	0.60 / (0.271)	0.55 / (0.25)	0.37 / (0.17)	0.55 / (0.25)
	<b>Direct Liquid</b>	10.34 / (4.69)	10.34 / (4.69)	9.42 / (4.28)	5.97 / (2.71)	7.35 / (3.34)	8.00 / (3.64)	6.82 / (3.10)	6.35 / (2.88)
	<b>Push-Pull Liquid</b>	10.08 / (4.58)	16.59 / (7.54)	14.50 / (6.59)	11.00 / (4.99)	31.46 / (14.30)	15.00 / (6.82)	9.15 / (4.16)	11.40 / (5.17)
<b>R134a</b>	<b>Direct Vapor</b>	<b>0.62 / (0.28) Fastest</b>	0.46 / (0.21*)	0.37 / (0.17)	0.42 / (0.19)	0.50 / (0.228)	0.46 / (0.21)	0.35 / (0.16)	0.46 / (0.21)
	<b>Direct Liquid</b>	6.46 / (2.93)	8.14 / (3.70)	6.42 / (2.92)	4.03 / (1.83)	5.65 / (2.57)	5.10 / (2.32)	5.35 / (2.43)	4.52 / (2.05)
	<b>Push-Pull Liquid</b>	11.90 / (5.40)	15.84 / (7.20)	11.75 / (5.34)	11.64 / (5.28)	25.61 / (11.64)	10.41 / (4.73)	6.93 / (3.15)	10.89 / (4.94)
<b>R410a</b>	<b>Direct Vapor</b>	<b>0.73 / (0.33) Fastest</b>	0.55 / (0.25)	0.37 / (0.17)	0.55 / (0.25)	0.70 / (0.319)	0.48 / (0.22)	0.35 / (0.16)	0.55 / (0.25)
	<b>Direct Liquid</b>	12.33 / (5.59)	17.16 / (7.80)	7.66 / (3.48)	3.55 / (1.61)	8.05 / (3.66)	10.56 / (4.80)	9.24 / (4.20)	5.71 / (2.59)
	<b>Push-Pull Liquid</b>	15.92 / (7.20)	20.46 / (9.30)	15.51 / (7.05)	17.39 / (7.89)	31.64 / (14.38)	15.25 / (6.93)	10.89 / (4.95)	15.85 / (7.19)
<b>R407c</b>	<b>Direct Vapor</b>	<b>0.73 / (0.33) Fastest</b>	0.55 / (0.25)	0.51 / (0.23)	0.55 / (0.25)	0.53 / (0.24)	0.53 / (0.24)	0.31 / (0.14)	N/A
	<b>Direct Liquid</b>	11.36 / (5.15)	11.90 / (5.41)	7.17 / (3.26)	5.49 / (2.49)	7.14 / (3.42)	7.81 / (3.55)	7.52 / (3.42)	N/A
	<b>Push-Pull Liquid</b>	11.56 / (5.24)	17.58 / (7.99)	14.52 / (6.60)	14.0 / (6.35)	29.08 / (13.22)	13.51 / (6.14)	10.03 / (4.56)	N/A

Industry's Fastest In Vapor Recovery

\* Using optional cooling coil accessory

\* Using optional water cool accessory MT69 in ice

lbs/min / (kg/min)

Disclaimer: The information found within this chart is not reflective of all competitors. All trademarks and copyrights on this page are owned by their respective owners. Data collected from technical specification literature available through the worldwide web and other publicly available marketing literature. © 2017 Fieldpiece Instruments. March 22, 2017. All Rights Reserved.



Distributed by:  
**Valuetesters.com**  
sales@valuetesters.com

Tel: 602-795-8292, Fax: 602-795-4624

[www.fieldpiece.com](http://www.fieldpiece.com)