



Whisper[®] Ultrasonic Leak Detector

VERSATILITY AND FLEXIBILITY FOR A VARIETY OF APPLICATIONS

Do you have a non-traditional leak detection application that a gas detector, soap bubbles or dye injection system can't address? Whisper is ideal for detecting and locating ultrasonic frequencies generated when the following common situations occur:

- leaks of any gas under pressure or vacuum
- electrical arcing
- worn bearings and machinery
- malfunctions in steam traps
- leaking seals

The leak detector includes a specialized built-in receiver that detects frequencies in the 40.5 kHz range. Through sophisticated circuitry, Whisper locates the ultrasound's source, while an internal noise control ensures the instrument is unaffected by audible noise. This makes Whisper a versatile tool which can even be used in noisy environments, such as mechanical rooms.



Whisper incorporates heterodyne capability, which reduces the ultrasonic frequencies detected to a range that can be heard by the human ear. Variations can therefore be identified to easily pin-point the ultrasonic source. Heterodyne output is enabled when headphones (included) are plugged in to the detector. Sensitivity is adjusted through an innovative touch pad. Multiple LEDs and an audible alarm register the leak when heterodyne mode is not enabled.

APPLICATIONS AT A GLANCE

- Refrigerant leaks
- Nitrogen leaks
- Locating worn bearings
- Leaks in pneumatic systems
- Leaks in compressed air systems
- Leaks in vacuum systems
- Diagnosing solenoid operations
- Steam traps
- Leaks in sealed areas (refrigerator cases, vehicles, etc.)
- Electrical arcing

Made in the USA

For the ultimate in performance and versatility, consider the Whisper with Accessory Package. Along with the leak detector, this kit gives you more accessories for more productivity. Use the contact probe to check machinery's function. Simply twist the metal probe onto the instrument and touch it to bearing housings, solenoids, pistons and other mechanical equipment to allow frequencies to travel into the Whisper's ultrasonic transducer. Properly functioning machinery sounds smooth and clear, a sharp contrast to malfunctioning machinery.



Whisper transmitter included with accessory package.

Use the transmitter to test seals around any enclosed space, including doors, windows, ducts and refrigerator cases. Simply turn the transmitter on to generate its ultrasonic tone and place it in the area you wish to leak test. Trace around potential problem areas with the Whisper leak detector to alert you to the transmitter's ultrasonic frequencies "leaking" through poorly-sealed areas.

The transmitter and contact probe as well as premium headphones are included in the accessory package, though any can be purchased separately for use with the standard package.

SPECIFICATIONS

Base unit includes	Headphones, rubber extension probe, (2) "D" alkaline batteries, hard plastic carrying case
Unit with accessory package includes	Premium headphones, metal contact probe, rubber extension probe, transmitter accessory with 9V battery, (2) "D" alkaline batteries, enlarged hard plastic carrying case
Controls	Power button, sensitivity touch pad
Power source	(2) "D" alkaline batteries (included)
Battery life	165 hours
Weight with batteries	1.5 lbs (680 g)
Warranty	2-year replacement

ORDERING INFORMATION

Whisper – Standard package	711-202-G1
Whisper – Accessory package	711-203-G1

Replacement Parts

Headphones	032-0404
Premium Headphones	032-0427
Ultrasonic Transmitter	711-600-G1
Contact Probe	711-316-G1

Distributed by:

 sales@valuetesters.com
 Tel: 602-795-8292, Fax: 602-795-4624



Whisper shown with contact probe (included with accessory package).

 **INFICON** Laboratory Accurate. Toolbox Tough®

www.inficonservicetools.com service.tools@inficon.com

Whisper is a registered trademark of INFICON GmbH.

Due to our continuing program of product improvements, specifications are subject to change without notice.

eibb05a1-b ©2012 INFICON