



GREENLEE.
A Textron Company

MADE FOR THE TRADE!™



TESTER, SIDEKICK T&ND

Sidekick T&ND Test Set

Distributed by:
Valuetesters.com
sales@valuetesters.com
Tel: 602-795-8292, Fax: 602-795-4624

Cat No: 50608530

UPC No: 783310608530

Description

- Easy-to-read digital LCD display
- Internal Dialer for making Transmission Test connections
- Autotest - performs 22 individual tests at the touch of a button
- Determines the stressed noise susceptibility of dry and working pairs
- Measures AC/DC Volts, Leakage, resistance, and loop current
- Performs circuit loss, circuit noise (metallic noise), and power influence tests
- Built-in open meter
- Locates up to 4 load coils
- Single set up for Tip-Ring, Tip-Ground, and Ring-Ground tests
- Field replaceable test leads
- On-screen display of "LOW BATTERY" when batteries are near failure

Specifications

- AC Voltage : 300 Vrms max.
- Circuit Loss : +1 to -15 dB
- Circuit Noise : 0 - 75 dBmC
- DC Voltage : \pm 300 Volts max.
- Dimensions : 10.750 IN x 4.250 IN x 2.500 IN
- Leakage : 100 Megohm max.
- Load Coil : Up To 4
- Loop Current : 0 - 100 mA
- Open : 0 To 60 kft.
- Power : Four AA Batteries
- Power Influence : 40 - 100 dBmC
- Resistance : 1 Megohm max.
- Stress Balance : 0 - 82 dBmC
- Sub Brand : Sidekick
- Type : T And ND Series
- Weight : 2.000 LB