



# Infrared temperature measuring instrument

testo 826



---

Non-contact measurement of surface temperature, ideally suitable for the food sector

---

6:1 optics for fast and accurate measurement

---

1-point laser measurement spot marking

---

Combined instrument with infrared and penetration measurement

---

Two adjustable limit values

---

Waterproof and robust thanks to dishwasher-safe protective cover TopSafe, according to protection class IP65

---

Hold function and display of min./max. values

---



**HACCP from every point of view:** the testo 826 series has just been optimized. A higher resolution thanks to the new processor ensures even more accurate measurement results. This allows the temperature to be recorded to an accuracy of 0.1 °C. The min./max. display shows the limit values of the last measurement. You can measure and monitor the temperature of the goods reliably and safely.

#### The advantages:

- Always monitor, measure and document temperature accurately, cleanly and quickly.
- Fulfil HACCP regulations, and be able to provide proof at any time.
- Maintain the cold chain in storage and transport.
- Reduce the quantities of spoiled goods and use resources efficiently.
- Measuring instruments calibrated according to strict regulations.
- Conform to HACCP as well as EN 13485.

## Technical data

### testo 826-T2

testo 826-T2, infrared thermometer with 1 point laser sighting, alarm function, incl. TopSafe and wall/belt holder

Part no. 0563 8282



### testo 826-T4

testo 826-T4, infrared thermometer with penetration probe, 1 point laser sighting, alarm function, incl. TopSafe, wall/belt holder, probe protection cap and frozen food drill

Part no. 0563 8284



#### General technical data

Spectral range	8 to 14 $\mu\text{m}$
Measurement rate	0,5 s
Distance to measurement spot	6:1
Emissivity	0,1 to 1
Meas. spot marking	1-point laser
Operating temperature	-20 to +50 °C
Storage temperature	-40 to +70 °C
Battery type	2 AAA micro batteries
Battery life	Approx. 20 h
Dimensions	148 x 34.4 x 19 mm
Display	LCD, 1 line
Weight	80 g
Standard	EN 13485
Warranty	2 years

Sensor types	Infrared	NTC (testo 826-T4)
Measuring range	-50 to +300 °C	-50 to +230 °C
Accuracy $\pm 1$ digit	$\pm 1.5$ °C (-20 to +100 °C) $\pm 2$ °C or 2% of mv (remaining range)	$\pm 0.5$ °C (-20 to +99.9 °C) $\pm 1$ °C or 1% of mv (remaining range)
Resolution	0.1 °C	0.1 °C
Spectral range	8 to 14 $\mu\text{m}$	
Measurement rate	0,5 s	1,25 s

## Accessories

#### Accessories for measuring instrument testo 826-T2 + testo 826-T4

#### Part no.

ISO calibration certificate/temperature for air/immersion probes, calibration point -18°C	0520 0061	
ISO calibration certificate/temperature for air/immersion probes, calibration point 0°C	0520 0062	
ISO calibration certificate/temperature For air/immersion probes, calibration points -18°C; +60°C	0520 0043	
ISO calibration certificate/temperature for air/immersion probes, calibration points -18°C; 0°C; +60°C	0520 0001	
ISO calibration certificate/temperature infrared thermometers, calibration points -18°C, 0°C, +60°C	0520 0401	
ISO calibration certificate temperature Infrared thermometers, calibration points 0°C, +60°C	0520 0452	

Distributed by:  
 **Valuetesters.com**  
 sales@valuetesters.com  
 Tel: 602-795-8292, Fax: 602-795-4624

