

Residential HVAC

Combustion Analyzers Selection Guide

Distributed by:
 **Valuetesters.com**
 sales@valuetesters.com
 Tel: 602-795-8292, Fax: 602-795-4624



PARAMETERS	S500-1	S500-2	S500-2P	S1500-NP	S1500-P
# of Gases	2	2-3	2-3	2	2
O ₂ Long Life, 0 - 25.0%	-	-	-	✓	✓
O ₂ Standard Sensor	✓	✓	✓	-	-
CO ₂ (Calculated from O ₂), 0 - 100%	✓	✓	✓	✓	✓
CO Measurement w/ NOx Filter, 0 - 4000 ppm	✓	✓	✓	-	-
CO Measurement w/ NOx Filter, 0 - 8000 ppm	-	-	-	✓	✓
Calculated Combustion Efficiency	✓	✓	✓	✓	✓
Ambient Temperature Measurement	✓	✓	✓	✓	✓
Stack Temperature Measurement	✓	✓	✓	✓	✓
Pressure Manometer	✓	✓	✓	✓	✓
Draft Measurement	✓	✓	✓	✓	✓
Excess Air	✓	✓	✓	✓	✓
Ambient CO Monitor	✓	✓	✓	✓	✓
CO Air Free	✓	✓	✓	✓	✓
High Altitude Adjustment	✓	✓	✓	✓	✓

FEATURES

Built-In Printer (Non-Fading Paper)	-	-	-	-	✓
Wireless Bluetooth® Printer	-	Optional	✓	Optional	-
FIELD-REPLACEABLE Pre-Calibrated Sensors	✓	✓	✓	✓	✓
Mobile App + QR code	(*)	(*)	(*)	✓	✓
PC Software	-	-	-	✓	✓
Combustion Efficiency Measurements for All Atmospheric & Condensing Systems	✓	✓	✓	✓	✓
Internal Memory (# of Tests)	5	5	5	2000	2000
Rechargeable Battery w/ AC Charger	✓	✓	✓	✓	✓
Display Screen	One color	One color	One color	Multicolor	Multicolor
Carrying Case	Hard	Hard	Hard	Hard	Hard

(*): Mobile App only for QR code