

New

Combination leak detector

testo 515 Ex – Combination leak detector for refrigerants and flammable gases with SGS certification.



ppm

Vol. %

%LEL

– High sensitivity

Detects leak rates down to 1 g/a

– Fast

Advanced fan suction for rapid response and recovery time < 2sec

– Convenient

Leak detection via flexible and robust gooseneck

– Easy & reliable

Selectable colored display modes (numeric, bar graph, trend curve) for intuitive leak analysis

– 2-in-1

Detection of refrigerants and flammable gases

– Safe

Operation in potentially explosive environments (Zone 2) via SGS/UL CSA 60079-0, UL/SA 60079-11 certification

– Alerting

Audio and vibration alarms

The testo 515 Ex combines fast and reliable performance with user-friendly design.

Leak rates down to 1 g/a can be detected, ensuring high sensitivity and long-term sensor stability.

An advanced fan suction delivers response and recovery times of less than 2 seconds, enabling fast leak localization.

The flexible gooseneck allows safe and reliable detection even in tight or difficult-to-access areas.

Selectable display modes with color graph and trend curve visualization enable clear monitoring of leak progression and precise pinpoint detection.

Interchangeable sensors enable 2-in-1 detection of refrigerants and flammable gases.

SGS certification ensures safe and reliable operation in potentially explosive environments.

Technical data

testo 515 Ex

Detection parameters	ppm, Vol. %, %LEL
Gases	methane, propane, butane, hydrogen (forming gas)
Refrigerants	HCFC, HFC, HFO, HCFO, HC (R290), and blends
Detection range	methane: 1 ppm ... 1,0 Vol. % CH ₄ propane: 1 ppm ... 1,0 Vol. % C ₃ H ₈ butane: 1 ppm ... 1,0 Vol. % C ₄ H ₁₀ hydrogen: 1 ppm ... 1,0 Vol. % H ₂
Resolution	1 ppm 0.1 Vol. % (> 999 ppm)
Response time	< 2 sec
Leak alarm	optical, audible, vibration
Sensitivity	1 g/a – High+ 3 g/a – High 14 g/a – Low
Sensor life	2 years under normal usage

General technical data

Operating temperature	-10 ... +122 °F
Operating humidity	10 ... 80 %rH
Storage temperature	- 4 ... +140 °F
Battery type	1800 mAh rechargeable Lithium-ion battery
Battery life	8 h
Dimensions	5.2 x 2.36 x 1.46 in (L x W x H)
Probe length with sensor	12 in
Weight	10.26 oz
Ex protection	SGS/UL CSA 60079-0, UL/CSA 60079-11, Zone 2



Device models & accessories

Device models

testo 515 Ex – Refrigeration

Combination leak detector for refrigerants (including propane) with SGS



- Softcase
- Filters
- Protection cap
- 1x Refrigeration sensor
- USB-C cable

Order number
0563 2515 01

testo 515 Ex – Gas

Combination leak detector for flammable gases with SGS



- Softcase
- Filters
- Protection cap
- 1x Gas sensor
- USB-C cable

Order number
0563 1515 01

testo 515 Ex – Gas & Refrigeration

Combination leak detector for flammable gases and refrigerants with SGS



- Softcase
- Filters
- Protection cap
- 1x Gas sensor
- 1x Refrigeration sensor
- USB-C cable

Order number
0563 0515 01

Accessories

Gas sensor



Order number
0554 3515

Refrigeration sensor



Order number
0554 4515