## 4-VALVE ALUMINUM MANIFOLD

## **Product Specifications**

Item Numbers/Product Descriptions						
Refrigerants	With 60" Hoses and Ball Valve Adapters	Without Hoses	Temp.	Pressure Range Low	Pressure Range High	
R410A	1839109 4V410H	1839111 4V410	F/C	-30" HG/300/ 500 psi	0/800 psi	
HP22-407C-410A (Heat Pump)	1839128 4V22407410	1839129 H 4V22407410		0/800 psi	0/800 psi	
R22-404A-410A	1839130 4V22404410	1839132 H 4V22404410	F	-30" HG/300/ 500 psi	0/800 psi	
Accuracy Class 1 - 1% Accuracy (full scale)						
Gauge Connection Type		1/8" NPT Male Fitting				
Valve Type	Doub	e O-ring Piston Style	:			
Valve Seat (Orifice)	alve Seat (Orifice) Replaceat		ble Stainless Steel (SAE-style straight thread with O-ring)			
Sight Glass Bonde		steel with SAE-style straight thread with O-ring				
Vacuum Port 3/8" full		ull bore (quantity 1)	bore (quantity 1)			
Charge Ports	harge Ports 1/4" (quar		ntity 3)			
Hoses Included	1839	1839143 H60BVS4 60" Hoses with Ball Valve Adapters - Set of 4				
Dimensions						
Length Width Height Weight	8-7/8" 4" 7-1/8" without hool 7.1 lbs.	8-7/8" 4" 7-1/8" without hook 3.4 lbs.				