

## Twister® Pro WIRE CONNECTOR

MODEL 344®

MADE IN

GLOBAL COMPONENTS

2 #16 w/1 #18 w/1 to 3 #22

2 #16 w/1 #18 w/1 to 3 #20

3 #16 w/1 to 2 #22 w/1 #20

3 #16 w/1 #18 w/1 to 2 #22

3 #16 w/1 #18 w/1 to 2 #20

4 #16 w/1 #22 w/1 #20

4 #16 w/1 #18 w/1 #22

4 #16 w/1 #18 w/1 #20

5 #16 w/1 #22, #20 or #18

1 #18 w/1 to 5 #22 or #20

1 #20 w/1 #22 w/1 to 3 #18

1 #20 w/2 #22 w/1 to 3 #18

2 #20 w/1 #22 w/1 to 3 #18

2 #18 w/1 to 4 #22, #20

3 #18 w/1 to 3 #22 or #20

4 #18 w/1 to 2 #22 or #20 5 #18 w/1 #22 or #20

1 #20 w/2 to 5 #22

2 #20 w/1 to 4 #22

3 #20 w/1 to 3 #22

4 #20 w/1 to 2 #22

30-244J

30-644.1

30-944

5 #20 w/1 #22

4 #16 w/1 to 2 #22, #20 or #18

2 #16 w/1 to 4 #20, #22 or #18

3 #16 w/1 to 3 #22, #20 or #18

## FEATURES/BENEFITS:



SUREGRIP™ OVERMOLDING PROVIDES IMPROVED LEVERAGE, MORE TORQUE, AND FASTER CONNECTIONS

COMFORTABLE SWEPT WINGS EASE HAND FATIGUE

EXPANDING SQUARE-WIRE SPRING PROVIDES A SECURE CONNECTION EVERY TIME

TOUGH, UL 94V-2 FLAME-RETARDANT SHELL RATED AT 105°C (221°F)

## **ELECTRICAL**

VOLTAGE GENERAL:

600 V MAX\*

1000V MAX IN FIXTURES AND SIGNS

PHYSICAL: STANDARDS & SPECIFICATIONS HOUSING: THERMOPLASTIC POLYPROPYLENE WITH

THERMOPLASTIC ELASTOMER

INSERT: STEEL PLATING: ZINC

TEMPERATURE: 105° C (221° F)

WIRE RANGE & COMBINATIONS:

- Solid and/or stranded wire combinations unless stated otherwise

UL 94V-2 FLAME RETARDANT

CSA CERTIFIED TO C22.2 No. 188-18

- Consult website for other combinations not listed

RoHS COMPLIANT

SHELL



1 #6 w/1#10 w/ 1 #14 3 #10 w/1 to 3 #18 1 #8 w/1 to 5 #16 3 #10 w/1 to 3 #16 1 #8 w/1 to 4 #14 3 #10 w/1 to 2 #14 1 #8 w/1 to 3 #12 3 #10 w/1 #12 1 #8 w/2 #12 w/1 to 2 #14 1 #8 w/1 to 2 #10 1 #8 w/1 #10 w/1 to 2 #14, #12 3 #10 w/1 #14 w/1 #16 3 #10 w/1 #12 w/1 #18 1 #8 w/2 #10 w/1 #14

1 #10 w/1 to 5 #18, #16 or #14 1 #10 w/1 or 4 #12 1 #10 w/1 #16 w/1 to 4 #18 1 #10 w/1 #14 w/1 to 4 #16 or #18 1 #10 w/2 #14 w/1 to 3 #16 1 #10 w/1 #12 w/1 to 4 #14 1 #10 w/1 #12 w/1 to 4 #16 or #18

3 #10 w/1 #16 w/1 to 2 #18 3 #10 w/1 #14 w/1 to 2 #18 3 #10 w/1 #12 w/1 #16 1 #12 w/1 to 5 #18, #16 or #14 1 #12 w/1 #16 w/1 to 3 #18 1 #12 w/1 #14 w/1 to 3 #18 1 to 2 #12 w/1 #14 w/1 to 3 #16 1 #12 w/2 #14 w/1 to 2 #16 2 #12 w/1 #14 w/1 to 3 #18 2 #12 w/1 #16 w/1 to 3 #18 2 #12 w/2 #14 w/1 to 2 #16

2 #14 w/1 #16 w/1 to 3 #18 2 #14 w/1 to 4 #22 or #20 2 #14 w/1 to 4 #18 or #16 3 #14 w/1 to 3 #22 or #20 3 #14 w/1 to 3 #18 or #16 3 #14 w/1 #16 w/1 to 2 #18 4 #14 w/1 to 2 #22 4 #14 w/1 to 2 #20, #18 or #16 4 #14 w/1 #16 w/1 #18 5 #14 w/1 #18 or #16 1 #16 w/1 to 5 #22, #20 or #18 1 #16 w/1 #20 w/1 to 2 #22 1 #16 w/2 #20 w/1 to 2 #22 1 #16 w/1 #18 w/1 to 3 #22 1 #16 w/1 #18 w/1 to 3 #20

ORDERING INFORMATION: QUANTITY

BOX OF 50

JAR OF 250

JAR OF 500

**BARREL OF 20,000** 

2 #16 w/1 #20 w/1 to 2 #22 2 #16 w/2 #20 w/1 to 2 #22

CAT NO WEIGHT (lbs) 30-144 0.5

2.1

43

154

**FACTORY CONTACT:** 

**DIMENSIONS:** 

SALES CONTACT:

Revised: September 2024