

YELLOW JACKET®

Series 41 2-Valve Manifold with 2-1/2" (63.5 mm) Gauges - °F




Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

Flutterless™ technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings.

Sliding double "O" ring pistons reduces wear. Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B).

Limited lifetime warranty on manifold bar and valves - not gauges. See warranty information for details.

Made in the USA 

Distributed by:

| Box | Clamshell | | | |
|------------|-----------|--|-------------|-------------------------|
| UPC# | UPC# | Description - °F/°C - Solar Gauges | Scale | Refrigerant |
| | 41612 | Manifold only | bar/psi/MPa | R-22/134a/404A/ |
| | 41615 | With 60" PLUS II™ standard fittings | bar/psi/MPa | 407C/409A/410A/438A/507 |
| UPC# | UPC# | Description - °F - Red/Blue | Scale | Refrigerant |
| | 41212 | Manifold only | psi | |
| 41213 | - | With 36" PLUS II™ standard fittings | psi | |
| 41220 | - | With 48" PLUS II™ standard fittings | psi | |
| | 41215 | With 60" PLUS II™ standard fittings | psi | |
| | 41219 | With 72" PLUS II™ standard fittings | psi | R-12/22/502 |
| | 44215 | With 60" PLUS II™ SealRight fittings | psi | |
| 44219 | - | With 72" PLUS II™ SealRight fittings | psi | |
| 42215 | - | With 60" PLUS II™ compact ball valve fittings | psi | |
| 42219 | - | With 72" PLUS II™ compact ball valve fittings | psi | |
| NEW | 41202 | Manifold only | psi | |
| | 41209 | With 36" PLUS II™ standard fittings | psi | R-22/134a/404A |
| | 41211 | With 60" PLUS II™ standard fittings | psi | |
| | 41312 | Manifold only | psi | |
| 41313 | - | With 36" RYB | psi | |
| 41311 | - | With 48" RYB | psi | |
| | 41315 | With 60" PLUS II™ standard fittings | psi | |
| | 41319 | With 72" PLUS II™ standard fittings | psi | |
| 43313 | - | With 36" PLUS II™ standard fittings | psi | |
| 44313 | - | With 36" PLUS II™ SealRight fittings | psi | R-134a/404A/507 |
| | 44315 | With 60" PLUS II™ SealRight fittings | psi | |
| 44319 | - | With 72" PLUS II™ SealRight fittings | psi | |
| 42315 | - | With 60" PLUS II™ compact ball valve fittings | psi | |
| | 41712 | Manifold only | bar/psi | |
| | 41709 | With 60" PLUS II™ standard fittings | bar/psi | |
| 41715* | - | With 60" PLUS II™ standard fittings for R-410A | bar/psi | |
| 41710 | - | With HCA 60" PLUS II™ standard fittings | bar/psi | R-410A |
| 41702 | - | With HCABV 60" PLUS II™ standard fittings | bar/psi | |
| 42715 | - | With 60" PLUS II™ compact ball valve fittings | bar/psi | |
| 41711* | - | With 60" PLUS II™ compact ball valve fittings for R-410A | bar/psi | |

* Special R-410A hose - R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.

