

# IPAQ R530

## Smart HART-compatible 2-wire Transmitter



IPAQ R530 is a modern, HART® temperature transmitter developed to meet the highest standards of accuracy and reliability. A universal transmitter compatible with RTD, thermocouples, voltage and potentiometer sensors. It is fully compatible with HART® 7 and offers extended diagnostic information, for example device error, sensor and wiring conditions.

IPAQ R530 supports communication via NFC® (Near-field communication) and Bluetooth® which makes it possible to configure and monitor the transmitter remotely.


- High accuracy and long term stability
- Accepts RTD, T/C, mV and ohm
- Sensor error correction
- 50-point Customized Linearization and Callendar-Van Dusen
- Low temperature drift
- High security - Password protection and date of changes logged
- Configuration via USB, without external power
- Runtime counter - hour counter for elapsed operational time
- Communicates with HART Communicator or PC via HART modem
- Integrated in Emerson AMS and Siemens PDM systems

### Specifications:


<b>Input RTD</b>		2-, 3-, 4-wire connection
Pt100 (α=0.00385) <sup>1)</sup>		-200 to +850 °C / -328 to +1562 °F
PtX 10 ≤ X ≤ 1000 (α=0.00385) <sup>1)</sup>		-200 to +850 °C / -328 to +1562 °F
Pt100 (α=0.003916) <sup>2)</sup>		-200 to +850 °C / -328 to +1562 °F
Ni100 <sup>3)</sup> , Ni120 <sup>4)</sup>		-60 to +250 °C / -76 to +482 °F
Ni1000 <sup>3)</sup>		-50 to +180 °C / -58 to +356 °F
Cu10 <sup>5)</sup>		-50 to +200 °C / -58 to +392 °F
<b>Input Resistance / potentiometer</b>		0 to 10000 Ω / 100 to 10000 Ω
<b>Input Thermocouples</b>		Types B, C, D, E, J, K, N, R, S, T
<b>Input mV</b>		-10 to +1000 mV
<b>Sensor failure</b>		Upscale (≥21.0 mA) or downscale (≤3.6 mA) action
<b>Adjustments - Zero</b>		Any value within range limits
<b>Adjustments - Minimum spans</b>		
Pt100, Pt1000, Ni100, Ni1000		10 °C / 18 °F
Resistance / potentiometer		10 Ω / 10 %
T/C, mV		2 mV
<b>Output</b>		4-20 mA / 20-4 mA, temperature linear
<b>Operating temperature</b>		-40 to +85 °C / -40 to +185 °F
<b>Galvanic isolation</b>		1500 VAC, 1 min
<b>Power supply</b>	IPAQ R530	8.5...36.0 VDC
	IPAQ R530X	8.5...30.0 VDC
<b>Intrinsic safety</b>		
IPAQ R530X ATEX:		II 1G Ex ia IIC T6...T4 Ga
IPAQ R530X IECEx:		Ex ia IIC T6...T4 Ga
IPAQ R530X FM US:		IS CL I Div 1 GP A-D, T6...T4 <sup>4)</sup>
IPAQ R530X FM CA:		Cl I Zn 0 AEx/Ex ia IIC T6...T4 Ga <sup>4)</sup>
<b>Typical accuracy</b>		±0.08°C or ±0.08% of span
<b>Mounting</b>		35 mm DIN rail acc. to EN 60715

<sup>1)</sup> IEC 60751, <sup>2)</sup> JIS C 1604, <sup>3)</sup> DIN 43760, <sup>4)</sup> Edison No. 7, <sup>5)</sup> Edison No. 15, <sup>6)</sup> T6...T4 are depending on effect


### Input connections




### Output connections



### Output load diagram



### Dimensions



### Ordering information

IPAQ R530	70R5300010
IPAQ R530X (ATEX, IECEx)	70R530X010
IPAQ R530X (cFmus, ATEX, IECEx)	70R530F010
ICON-X, PC configuration kit	70CFGUSX01
ICON-BT, Bluetooth® configuration kit	70CFGBT001