


Non-Insulated Female Disconnect Dimensions



Wire Range (AWG)	Wire Range (mm ²)	Tab Size (in.)	Tab Size (mm)	Dimensions (in.)				Dimensions (mm)				Cat. No
				L	B	W	F	L	B	W	L	
22-18	0.5 - 1.0	.110 x .020	2.8 x 0.5	.630	.189	.126	.256	16.0	4.8	3.2	6.5	83-9411
16-14	1.5 - 2.5	.110 x .020	2.8 x 0.5	.630	.189	.126	.256	16.0	4.8	3.2	6.5	83-9421
22-18	0.5 - 1.25	.187 x .020	4.75 x 0.5	.630	.189	.197	.252	16.0	4.8	5.0	6.4	83-9441
16-14	1.5 - 2.5	.187 x .020	4.75 x 0.5	.630	.189	.197	.252	16.0	4.8	5.0	6.4	82-9451
22-18	0.5 - 1.25	.250 x .032	6.35 x 0.8	.630	.189	.260	.287	16.0	4.8	6.6	7.3	83-9471
16-14	1.5 - 2.5	.250 x .032	6.35 x 0.8	.630	.189	.260	.287	16.0	4.8	6.6	7.3	83-9481
12-10	4.0 - 6.0	.250 x .032	6.35 x 0.8	.728	.236	.260	.287	18.5	6.0	6.6	7.3	83-9501

105°C/300 Volts max.