



FLIR Axxx-SERIES IMAGE STREAMING

Fixed-Mount Thermal Camera



Key Features:

- Robust and reliable thermal imaging for applications where temperature accuracy matters
- Easily incorporate thermal imaging into machine vision applications using standard industry protocols
- Full featured, flexible options allow camera configurations to meet specific application requirements

Main Applications:

- Productivity and quality assurance monitoring
- Continuous monitoring of electrical and mechanical systems
- Early fire detection for fast response

SPECIFICATIONS

<i>Detector Data</i>	Standard Configuration	Advanced Configuration
IR resolution	320 × 240 (A400), 464 × 348 (A500), or 640 × 480 (A700)	
Visual resolution	1280 × 960	
Focal plane array/spectral range	<30 mK to <50 mK, lens dependent	
Lenses	6°, 14°, 24°, 42°, 80°, FlexView® (24°/14°) or (42°/24°) lenses	
IR camera focus	One-shot contrast, motorized, manual	
<i>Measurement</i>		
<i>Object temperatures</i>	-20°C to 120°C (-4°F to 248°F) 0°C to 650°C (32°F to 1202°F) A400/A500: 300°C to 1500°C (572°F to 2732°F) A700: 300°C to 2000°C (572°F to 3632°F)	
Accuracy	±2°C (±3.6°F) or ±2% of reading	
<i>Video streaming, RTSP protocol</i>		
Unicast	-	Yes
Multicast	-	Yes
Multiple image streams	-	Yes
<i>RTSP protocol - video stream 0</i>		
Source	-	Visual, IR, MSX®
Contrast enhancement	-	FSX®, histogram equalization (IR only)
Overlay	-	With, without
Pixel format	-	YUV411
Encoding	-	H.264/MPEG4/MJPEG

<i>RTSP protocol - video stream 1</i>	Standard Configuration	Advanced Configuration
<i>Source</i>	-	Visual, IR, MSX
Overlay	-	No
Pixel format	-	YUV411
Encoding	-	H.264/MPEG4/MJPEG
<i>Radiometric streaming, RTSP</i>		
Source	IR	
Pixel format	MONO 16	
Encoding	Compressed JPEG-LS; FLIR radiometric	
<i>Video/radiometric streaming, GVSP (GigE Vision) protocol</i>		
Unicast	Yes	
Multicast	Yes	
Multiple image streams	No	
<i>Non-radiometric streaming, GVSP (GigE Vision) protocol</i>		
Resolution	Visual, IR, MSX, 640 × 480 pixels	
Contrast enhancement	FSX (optional), histogram equalization (IR only)	
Overlay	With, without	
Pixel format	YUV411 or MONO 8	
Encoding	Uncompressed	

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 09/25/24
RH24-0539-INS



FLIR Axxx-SERIES IMAGE STREAMING

Fixed-Mount Thermal Camera

SPECIFICATIONS, CONT.

	Standard Configuration	Advanced Configuration
<i>Radiometric streaming, GVSP (GigE Vision) protocol</i>		
Resolution	320 × 240 (A400), 464 × 348 (A500), or 640 × 480 (A700)	
Source	IR	
Pixel format	MONO 16	
Encoding	FLIR Radiometric, temperature linear, compressed JPEG-LS	
<i>Ethernet</i>		
Interface	Wired; Wi-Fi*	
Connector types	M12 8-pin X-coded, female; RP-SMA, female	
Ethernet type & standard	1000 Mbps, IEEE 802.3	
Ethernet power	Power over Ethernet, PoE IEEE 802.3af class 3	
Ethernet protocols	Include EtherNet/IP, Modbus TCP, and MQTT	
<i>Digital input/output</i>		
Connector type	M12 Male 12-pin A-coded (shared with ext. power)	
Digital input	2× opto-isolated, Vin (low) = 0-1.5 V, Vin (high) = 3-25 V	
Digital output	3× opto-isolated, 0–48 V DC, max. 350 mA (derated to 200 mA at 60°C). Solid-state opto relay, 1× dedicated as fault output (NC)	
<i>Power system</i>		
Connector type	M12 Male 12-pin A-coded (shared with Digital I/O)	
Power consumption	7.5 W at 24 V DC typical; 7.8 W at 48 V DC typical; 8.1 W at 48 V PoE typical	
<i>Wi-Fi*</i>		
Connector type	Female RP-SMA	

*Optional feature

The FLIR A-Series cameras are designed for configuration to your specific needs.
Specifications are subject to change without notice.

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact. ©2024 Teledyne FLIR, LLC. All rights reserved.

Revised 09/25/24
RH24-0539-INS