



Singlemode and multimode fibers

Dust bin safely collects end cuts

Cleave 250 micron, 900 micron, 3mm and Bowtie fibers



**Renewed** Vision. **Innovation** Forward.



# 920CL Fiber Optic Cleaver

## **BENEFITS:**

- Accurate Cleaves. Cleave multi-mode and single-mode fiber optic cables.
- Long Life. Blades rotate for longer life over 48,000 cleaves.
- Adaptable. Supports 250 micron, 900 micron, 3mm and Bowtie fibers.
- **Dust bin.** Safely collects end cuts during cleaving process.
- Fixed Clamp. For use as a standalone cleaver.



#### **SPECIFICATIONS:**

920CL	Fiber Type:	SM (G.652); MM (G.651); DS (G.653); NZDS (G.655); BIF (G.657)
	Fiber Cleave Length:	5mm - 20mm
	Cladding Diameter:	125µm
	Coating Diameter:	0.25mm and 0.9mm
	Fiber Count:	Single
	Cleaving Angle:	< 0.5°
	Blade Life:	48,000 Cleaves
	Weight:	0.68lbs (310g)
	Dimensions:	2.13 x 2.28 x 2.28" (54 x 58 x 58 mm)

\*Specifications subject to change without notice.

### ORDERING INFORMATION:

CAT. NO.	DESCRIPTION	
920CL	Fiber Optic Cleaver	
920CL CLVR Case	Cleaver Case	
01640	Cleaving Wheel	
FC920&200	Fixed Clamp 920CL & FCL200 With Screw	
04268	Replacement Screw for Fixed Clamp	

## **CONTENTS:**

• 920CL Cleaver with Fixed Clamp installed • 2.5mm Allen Key • Instruction Sheet • Hard Carry Case

TC6714 03/23



**Renewed** Vision. **Innovation** Forward.

