

C400 Series Controller Analyzer

Conductivity, TDS, Resistivity, Salinity



- ✓ Large LCD display
- ✓ Intelligent menu operation
- ✓ SimplCal® automatic calibration
- ✓ Manual + automatic temperature compensation
- ✓ Two (2) relays
- ✓ 4-20mA & RS485 outputs
- ✓ Multi-parameter display — simultaneously shows conductivity and temperature
- ✓ Password protection



High Performance Industrial Controller Analyzer

The ProCon® C400 series is an extremely robust industrial conductivity controller analyzer.

The modular design is both easy to install and operate providing first measurement values in under one minute.

The C400 is packed with all the extra features included, no need to pay extra for relays, 4-20mA or RS485 outputs.

The SimplCal® feature makes calibrating your sensor easier and quicker than ever before. The cost-saving quick and simple setup is done through our user-friendly step-by-step on-screen menu.

Active display of red alarm alert provides notification of out-of-bounds sensor readings and indication for sensor cleaning, recalibration or replacement.


Enclosure

The C400 is packaged in a rugged polycarbonate enclosure making it ideally suited for heavy-duty applications. A mounting kit is included for surface and panel mounting. Pipe mounting kits are available.

**Cable Grip
Wire Connector
Combo**
(no internal
wiring required)



SimplConnect™
Cable Grip Connectors



C400 Series Controller Analyzer

Conductivity, TDS, Resistivity, Salinity



ICON
PROCESS CONTROLS


Corrosion-Free
Instrumentation Equipment

Technical Specifications



Measuring Range	0 – 500mS/cm
Resolution	0.1µS/cm 0.01mS/cm
Intrinsic Error	±0.5% F.S
Resistivity	0 – 18.25MΩ/cm
Resolution	0.01KΩ/cm 0.01MΩ/cm
TDS	0 – 250g/L
Resolution	0.01mg/L 0.01g/L
Salinity	0 – 700ppt
Resolution	0.01ppm 0.01ppt
Working Temperature	32 – 302°F 0 – 150°C
Temperature Compensation	Automatic or Manual
Outputs	Two (2) 4–20mA 20–4mA 0–20mA
Communication	RS485 MODBUS RTU
Relay Control Contact	5A 240VAC 5A – 28VDC
Power Supply	9 – 36VDC (std) 85 – 265VAC Power Consumption 3W
Environmental Temperature	14 – 140°F -10 – 60°C
Relative Humidity	≤ 90%
Enclosure Rating	IP65
Weight	0.5kg
Dimensions	98 × 98 × 130mm
Installation Opening Size	93 X 93mm
Installation methods	Panel Pipe Wall

Dimensions



C400 Series Controller Analyzer

Conductivity, TDS, Resistivity, Salinity




ICON
PROCESS CONTROLS

Corrosion-Free
Instrumentation Equipment


Instrument Installation




Wall Mounting




Control Panel Installation



Installation of
back cover with
waterproofing seal



Typical Application



C400 Series Controller Analyzer

Conductivity, TDS, Resistivity, Salinity



ICON
PROCESS CONTROLS

Corrosion-Free
Instrumentation Equipment



**CANCEL
THE
CONDUCTIVITY
MODULE**

Model Selection

D400 — pH/ORP Controller (Color LED)

Part Number	Power	Output	Power Cord	Display 1	Display 2
D400-4-D-N-P-0	24VDC	4-20mA + 2 Relays	No	pH/ORP	Single Display
D400-4-D-Y-P-0	24VDC	4-20mA + 2 Relays	Yes	pH/ORP	Single Display

Communication: RS-485 RTU Modbus