



Empowering you to work smarter



Compatible with *myNAVAC™* App

NX4 NX4V NEXUS Digital Manifold Gauge



4 Valve



Smart and Precise

Smart and Wireless

- Work with myNAVAC™ App
- Bluetooth connections with temp probes & micron gauge (sold separately)

Digital and Accurate

- Class 0.4 accuracy with digital display
- Precision at a glance

Multi-Operation Modes

- Manifold mode with SH/SC display
- Pressure Test mode
- Evacuation mode

Aluminum Body w/ 1/4 Turn Ball Valve

- Reliable, efficient and durable
- Better work experience

4 Valves

- Includes a 3/8" vacuum port for fast evacuations
- Single setup for multi-task operations

Easy to Use

- Folding hook
- Impact-resistant rubber cover

Model	NX4 (Vacuum Gauge Not Included)	NX4V (Vacuum Gauge Included)
Refrigerant Type	R-11, R-12, R-13, R-22, R-23, R-32, R-113, R-114, R-115, R-116, R-123, R-124, R-125, R-134a, R-236fa, R-245fa, R-290, R-401A, R-401B, R-402A, R-402B, R-403B, R-404A, R-406A, R-407A, R-407B, R-407C, R-408A, R-409A, R-410A, R-413A, R-414A, R-414B, R-416A, R-417A, R-417C, R-420A, R-421A, R-421B, R-422A, R-422B, R-422C, R-422D, R-424A, R-427A, R-428A, R-434A, R-437A, R-438A, R-448A, R-449A, R-450A, R-452A, R-452B, R-453A, R-454B, R-458A, R-500, R-501, R-502, R-503, R-507A, R-508B, R-513A, R-600, R-600a, R-601, R-601a, R-744*, R-1233zd, R-1234yf, R-1234ze *Maximum pressure: 1087 psi (7500 kPa) Firmware can be updated at NAVAC website or with MyNAVAC™ App	
Ports	(1) 3/8" sae for evacuation; (3) 1/4" sae for suction line, liquid line, and refrigerant recovery/charging	
Maximum Manifold Pressure	1087 psi (7500 kPa)	
Power Supply	Rechargeable 3000mAh lithium battery	
Accessory	Bluetooth Temperature Clamps NST1 (Low Side), NST2 (High Side), Charging Cable, Carry Case	NMV1S Vacuum Gauge in addition to the NX4 Kit

2-YEAR WARRANTY